FEDERAL ITEM IDENTIFICATION GUIDE

PRINTER, AUTOMATIC DATA PROCESSING

ITEM NAME CODE

33792

This Reprint replaces FIIG A506K, dated December 7, 2007.

Commander

Defense Logistics Information Service

ATTN: DLIS-K

74 Washington Avenue North, Suite 7

Battle Creek, Michigan 49037-3084

(COMM) (269) 961-5779

(DSN) 661-5779

This Federal Item Identification Guide for Supply Cataloging is issued under the authority of Department of Defense Instruction 5025.7.

The use of this publication is mandatory for US. Federal Activities participating in Federal Catalog System Operations.

BY ORDER OF THE DIRECTOR

/s/

Commander

Defense Logistics Information Service

Table of Contents

SECTION I

MRC	Mode Code	Requirements
NAME	D	ITEM NAME

Definition: A NOUN, WITH OR WITHOUT MODIFIERS, BY WHICH AN ITEM OF SUPPLY IS KNOWN.

Reply Instructions: Enter the applicable Item Name Code. (e.g., NAMED33792*)

ALXW	D	PRINTER TYPE

Note: A reply to this MRC is required for Schedule B Code Assignment

Definition: INDICATES THE TYPE OF DEVICE USED FOR FORMING PRINT.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., ALXWDAMJ*)

REPLY CODE	REPLY (AE15)
AMJ	BAND (chain)
AMR	BUBBLE JET
AMK	DAISY WHEEL
AML	DOT MATRIX (line matrix)
AMM	INK JET
AMN	LASER
AMS	THERMAL

CPLR	D	UNIT DESIGN

Definition: THE DESIGN OF THE UNIT.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., CPLRDAFD*; CPLRDAFD$DAJR*)

REPLY CODE	REPLY (AK54)
AJQ	CABINET
FVC	DESK TOP
FWV	DRAWER MOUNTED
FUY	FREE STANDING
AFD	PANEL MOUNTED
AJR	PORTABLE
FVE	RACK MOUNTED

1

MRC	Mode Code	Requirements
CYEC	D	INTERFACE TYPE

Definition: INDICATES THE TYPE OF INTERFACE(S) AVAILABLE FOR INPUT/OUTPUT COMMUNICATIONS.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., CYECDGS*; CYECDGS$$DHC*)

REPLY CODE	REPLY (AE79)
DW	BNC
GS	CENTRONICS
GV	DB 25 FEMALE
GW	DB 25 MALE
GT	DB9
GU	DB15
GX	DEC 425
GY	DIN
JD	EDGE CONNECTOR
HF	ESDI
JC	IDE
GZ	IEEE 488
JG	IEEE 1284
HG	MFM
HA	RJ11
HB	RJ45
HH	RLL
HC	RS 232C
HD	RS 422
HJ	SCSI
JH	SCSI-1
JJ	SCSI-2
JN	USB
HE	1553

CSBH *	J	VOLTAGE IN VOLTS AND CURRENT TYPE

Definition: THE TOTAL ELECTRICAL VOLTAGE, EXPRESSED IN VOLTS, AND THE TYPE OF CURRENT WHETHER ALTERNATING OR DIRECT.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric value. (e.g., CSBHJDC12.0*; CSBHJDC12.0$$JAC120.0*)

REPLY CODE	REPLY (AN87)
AC	AC
DC	DC

MRC	Mode Code	Requirements

AFGA *   J   OPERATING TEMP RANGE

Definition: THE MINIMUM AND MAXIMUM LIMITS OF TEMPERATURE AT WHICH THE ITEM IS RATED FOR OPERATION.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric values separated by slash. Proceed negative values with a M and positive values with a P. (e.g., AFGAJCM55.0/P125.0*)

REPLY CODE	REPLY (AB36)
C	DEG CELSIUS
F	DEG FAHRENHEIT

CYGW *   J   BUFFER SIZE

Definition: DESIGNATES THE MAXIMUM SIZE OF THE TEMPORARY DATA STORAGE CAPABILITY OF THE ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric value. (e.g., CYGWJMT64.0*)

REPLY CODE	REPLY (AG67)
MT	BYTES
MU	CHARACTERS
ML	GIGABYTES
MM	KILOBYTES
MN	MEGABYTES

BMQK *   J   MAXIMUM PAPER SIZE ACCOMMODATED

Definition: DESIGNATES THE MAXIMUM PAPER SIZE THE ITEM IS DESIGNED TO ACCOMMODATE.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric values, separated by a slash. Precede each value with a P. (e.g., BMQKJAP8.0/P11.5*; BMQKJLP25.4/P27.8*)

REPLY CODE	REPLY (AA05)
A	INCHES
L	MILLIMETERS

CYGX *   D   PRINTING TYPE

3

MRC	Mode Code	Requirements

Definition: INDICATES THE TYPE OF PRINT THAT IS AVAILABLE.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., CYGXDASE*; CYGXDASE$$DFWW*)

REPLY CODE	REPLY (AK54)
GAH	BOLD
ASE	CONDENSED
FWW	DOUBLE HEIGHT
FWX	DRAFT
GAJ	EMPHASIZE
FWY	ENLARGED
FWZ	HIGH QUALITY
GAK	ITALIC
FXA	LETTER QUALITY
FXB	NEAR LETTER QUALITY (NLQ)
GAL	SUBSCRIPT
GAM	SUPERSCRIPT

AHDX *   J   RESOLUTION PRINTING DENSITY AND COLOR

Definition: INDICATES THE NUMBER OF PRINTED DOTS THE ITEM CAN PRINT ON A RATED AREA AND THE COLOR.

Reply Instructions: Enter the applicable Reply Codes from Tables 1, 2 and 3 below, followed by the numeric value. (e.g., AHDXJHXAAC360.0$$JHXBAC360.0$$JHXAAB720.0$$JHXBAB360.0*)

Table 1
REPLY CODE	REPLY (AB49)
HX	DOT DENSITY (DPI)

Table 2
REPLY CODE	REPLY (AA99)
A	HORIZONTAL
B	VERTICAL

Table 3
REPLY CODE	REPLY (AG38)
AB	BLACK AND WHITE
AC	COLOR

AHGC *   J   PRINT SPEED AND COLOR

MRC	Mode Code	Requirements

NOTE: A reply to this MRC is required for Schedule B Code assignment.

Definition: DESIGNATES THE PRINTING RATE OF THE ITEM AND THE COLOR.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., AHGCJACAPV0.52$$JABAPV4.00*)

Table 1

REPLY CODE	REPLY (AG38)
AB	BLACK AND WHITE
AC	COLOR

Table 2

REPLY CODE	REPLY (AB44)
APU	CHARACTERS PER SECOND
APV	PAGES PER MINUTE
APW	WORDS PER MINUTE

ABHP *   J   OVERALL LENGTH

Definition: THE DIMENSION MEASURED ALONG THE LONGITUDINAL AXIS WITH TERMINATED POINTS AT THE EXTREME ENDS OF THE ITEM.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABHPJAA3.500*; ABHPJLA25.4*; ABHPJAB2.500$$JAC3.500*)

Table 1

REPLY CODE	REPLY (AA05)
A	INCHES
L	MILLIMETERS

Table 2

REPLY CODE	REPLY (AC20)
A	NOMINAL
B	MINIMUM
C	MAXIMUM

ABKW *   J   OVERALL HEIGHT

Definition: THE DISTANCE MEASURED IN A STRAIGHT LINE FROM THE BOTTOM TO THE TOP OF AN ITEM.

MRC	Mode Code	Requirements

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABKWJAA2.750*; ABKWJLA25.4*; ABKWJAB2.000$$JAC2.750*)

Table 1

REPLY CODE	REPLY (AA05)
A	INCHES
L	MILLIMETERS

Table 2

REPLY CODE	REPLY (AC20)
A	NOMINAL
B	MINIMUM
C	MAXIMUM

ABMK *   J   OVERALL WIDTH

Definition: AN OVERALL MEASUREMENT TAKEN AT RIGHT ANGLES TO THE LENGTH OF AN ITEM, IN DISTINCTION FROM THICKNESS.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABMKJAA1.385*; ABMKJLA25.4*; ABMKJAB1.250$$JAC1.500*)

Table 1

REPLY CODE	REPLY (AA05)
A	INCHES
L	MILLIMETERS

Table 2

REPLY CODE	REPLY (AC20)
A	NOMINAL
B	MINIMUM
C	MAXIMUM

AKYD *   G   ACCESSORY COMPONENTS AND QUANTITY

Definition: THE NAME AND NUMBER OF PARTS SUPPLIED WITH THE ITEM WHICH MAY BE REQUIRED FOR APPLICATION.

Reply Instructions: Enter the reply in clear text. (e.g., AKYDGDATA CABLE 1*)

TMDN *   A   TYPE/MODEL DESIGNATION

6

MRC	Mode Code	Requirements

Definition: THE ALPHA-NUMERIC-ALPHA DESIGNATION USED TO IDENTIFY THE TYPE AND/OR MODEL OF THE BASIC ITEM.

Reply Instructions: Enter the appropriate designation data. (e.g., TMDNADESKJET 600*)

AGYH   D   PAPER FEED MECHANISM

Definition: INDICATES THE TYPE OF PAPER FEED.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., AGYHDFBU*; AGYHDFBU$$DFBW*)

REPLY CODE	REPLY (AN47)
FBU	AUTOMATIC SHEET FEEDER
FBV	FRICTION FEED
FBW	SHEET FEEDER
DRS	TRAY

AGYM * J   ADDITIONAL PROGRAMS

Definition: AN INDICATION OF THE ADDITIONAL PROGRAMS AVAILABLE WITH THE ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the edition designation and version number. (e.g., AGYMJFBY1*; AGYMJFBY1$$JFCA1*)

REPLY CODE	REPLY (AN47)
FBX	EMULATION
FBY	POSTSCRIPT
FBZ	PRINTER COMMUNICATION LANGUAGE (PCL)
FCA	TRUE TYPE

CBBL * D   FEATURES PROVIDED

Definition: THOSE FEATURES, NOT OTHERWISE SPECIFIED, WHICH MAY BE REQUIRED FOR PROPER FUNCTIONING OF THE ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., CBBLDDVB*; CBBLDDVB$$DDVC*)

For multiple replies, record in table sequence.

7

MRC	Mode Code	Requirements

REPLY   REPLY (AN47)
CODE
AZK   AC ADAPTER
DVB   CHANGEABLE FONTS
DVC   COLOR CAPABLE
DTL   CONTROLLER BOARD
DBN   ELECTROMAGNETIC INTERFERENCE
               SHIELDING (EMI)
DVD   EXPANDABLE BUFFER MEMORY
DVE   RECHARGEABLE BATTERY PACK
AGQ   RFI SHIELDING
CEN   RUGGEDIZED
DVF   SINGLE SHEET FEEDER
DMF   TEMPEST

PMLC *   J   PRECIOUS MATERIAL AND LOCATION

Definition: AN INDICATION OF THE PRECIOUS MATERIAL AND ITS LOCATION IN THE ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the location in clear text. (e.g., PMLCJAUA000TERMINALS*; PMLCJAUA000TERMINALS$$JAGA000 INTERNAL SURFACES*; PMLCJAUA000TERMINAL$JAGA000INTERNAL SURFACES*)

REPLY CODE   REPLY (MA01)
AUA000   GOLD
IRA000   IRIDIUM
AZA000   OSMIUM
PDA000   PALLADIUM
PTA000   PLATINUM
RHA000   RHODIUM
RTA000   RUTHENIUM
AGA000   SILVER

FEAT *   G   SPECIAL FEATURES

Definition: THOSE UNUSUAL OR UNIQUE CHARACTERISTICS OR QUALITIES OF AN ITEM NOT COVERED IN THE OTHER REQUIREMENTS AND WHICH ARE DETERMINED TO BE ESSENTIAL FOR IDENTIFICATION.

Reply Instructions: Enter the reply in clear text. (e.g., FEATGQUALITY CONTROLLED*)

8

MRC	Mode Code	Requirements

TEST *   J   TEST DATA DOCUMENT

Definition: THE SPECIFICATION, STANDARD, DRAWING, OR SIMILAR INSTRUMENT THAT SPECIFIES ENVIRONMENTAL AND PERFORMANCE REQUIREMENTS OR TEST CONDITIONS UNDER WHICH AN ITEM IS TESTED AND ESTABLISHES ACCEPTABLE LIMITS WITHIN WHICH THE ITEM MUST CONFORM IDENTIFIED BY AN ALPHABETIC AND/OR NUMERIC REFERENCE NUMBER. INCLUDES THE COMMERCIAL AND GOVERNMENT ENTITY (CAGE) CODE OF THE ENTITY CONTROLLING THE INSTRUMENT.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the 5-position CAGE code, a dash, and the document identification number. (e.g., TESTJA12345-CWX654321*; TESTJA12345-654321$$JB55566\N66354*; TESTJA12345-654321$JB55566-663654*)

REPLY CODE	REPLY (AC28)
A	SPECIFICATION (Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "nominal", etc.)
B	STANDARD (Includes industry or association standards, individual manufacturer standards, etc.)
C	DRAWING (This is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc; excludes any specification, standard, or other document that may be referenced in a basic governing drawing.)

ZZZK *   J   SPECIFICATION/STANDARD DATA

Definition: THE DOCUMENT DESIGNATOR OF THE SPECIFICATION OR STANDARD WHICH ESTABLISHED THE ITEM OF SUPPLY.

MRC	Mode Code	Requirements

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the Commercial and Government Entity (CAGE) Code of the entity controlling the document, a dash, and the document designator. The agency that controls the limited coordination document must be preceded and followed by a slash following the designator. The word canceled or superseded must be preceded and followed by a slash for the designator. Professional and industrial association specifications/standards are differentiated from a manufacturer's specification in that the data has been coordinated and published by the professional and industrial association. Include amendments and revisions where applicable.

(e.g., ZZZKJT81337-30642B*;

ZZZKJS81349-MIL-D-180 REV1/CANCELED/*;

ZZZKJP80205-NAS1103*;

ZZZKJS81349-MIL-C-1140C/CE/*;

ZZZKJT81337-30642B$$JP80205-NAS1103*)

REPLY CODE	REPLY (AN62)
S	GOVERNMENT SPECIFICATION
T	GOVERNMENT STANDARD
D	MANUFACTURERS SOURCE CONTROL
R	MANUFACTURERS SPECIFICATION
N	MANUFACTURERS SPECIFICATION CONTROL
M	MANUFACTURERS STANDARD
B	NATIONAL STD/SPEC
A	PROFESSIONAL/INDUSTRIAL ASSOCIATION SPECIFICATION
P	PROFESSIONAL/INDUSTRIAL ASSOCIATION STANDARD

ZZZT *   J   NONDEFINITIVE SPEC/STD DATA

NOTE: If the specification/standard cited in reply to MRC ZZZK is nondefinitive, reply to MRC ZZZT. This reply is the data which is not recorded in Segment C.

Definition: THE NUMBER, LETTER, OR SYMBOL THAT INDICATES THE TYPE, STYLE, GRADE, CLASS, AND THE LIKE, OF AN ITEM IN A NONIDENTIFYING SPECIFICATION OR STANDARD.

MRC	Mode Code	Requirements

Reply Instructions: Enter the applicable Reply Code from Appendix A , Table 1, followed by the appropriate number, letter, or symbol. (e.g., ZZZTJTY1*; ZZZTJTY1$$JSTA*; ZZZTJTY1$JSTA*)

ZZZY *   G   REFERENCE NUMBER DIFFERENTIATING CHARACTERISTICS

Definition: A FEATURE OF THE ITEM OF SUPPLY WHICH MUST BE SPECIFICALLY RECORDED WHEN THE REFERENCE NUMBER COVERS A RANGE OF ITEMS.

Reply Instructions: Enter the reply in clear text. (e.g., ZZZYGCOLOR CODED LEADS*; ZZZYGAS DIFFERENTIATED BY MATERIAL*)

CRTL *   A   CRITICALITY CODE JUSTIFICATION

Definition: THE MASTER REQUIREMENT CODES OF THOSE REQUIREMENTS WHICH ARE TECHNICALLY CRITICAL BY REASON OF TOLERANCE, FIT, PERFORMANCE, OR OTHER CHARACTERISTICS WHICH AFFECT IDENTIFICATION OF THE ITEM.

Reply Instructions: Enter the Master Requirement Code for the requirement, the reply to which renders the item as being critical. (e.g., CRTLAAKJA*; CRTLAAKJA$$ACSGS*)

Reply to this requirement only if the header record for the item identification for the item being identified has been coded as critical.

PRPY *   A   PROPRIETARY CHARACTERISTICS

NOTE: If Document Availability Code B, D, F, or H, reply to MRC PRPY.

Definition: IDENTIFICATION OF THOSE CHARACTERISTICS INCLUDED IN THE DESCRIPTION FOR WHICH A NON-GOVERNMENT ACTIVITY HAS IDENTIFIED ALL OR SELECTED CHARACTERISTICS OF THE ITEM AS BEING PROPRIETARY AND THEREFORE RESTRICTED FROM RELEASE OUTSIDE THE GOVERNMENT WITHOUT PRIOR PERMISSION OF THE ORIGINATOR OF THE DATA.

Reply Instructions: Enter the MRC codes of the individual characteristics of the description which are marked proprietary on the technical data, using AND coding ($$) for multiple characteristics. If all the MRCs are proprietary, enter the reply PACS. If none of the MRCs is proprietary, enter the reply NPAC. (e.g., PRPYAPACS*; PRPYANPAC*; PRPYAAKJA$$ACSGS*)

MRC	Mode Code	Requirements

NHCF *   D   NUCLEAR HARDNESS CRITICAL FEATURE

NOTE: If the Criticality Code is E, H, or M, reply to MRC NHCF.

Definition: AN INDICATION OF THE NUCLEAR HARDNESS CRITICALITY
OF THE ITEM.

Reply Instructions: Enter the reply code from the table below. (e.g., NHCFDCY*)

REPLY CODE   REPLY (AD05)
CY   HARDENED

ENAC *   D   ENVIRONMENTAL ATTRIBUTE CODE

NOTE: Answering this MRC will generate an ENAC Code in the Item Identification
Segment (A) of the NSN.

Definition: INDICATES THE TYPE OF PRODUCT THAT MEETS OR EXCEEDS
THE GOVERNMENT GUIDELINES FOR ENVIRONMENTALLY PREFERRED
CHARACTERISTICS.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g.,
ENACDFY*; ENACDHU$$DFY*)

REPLY CODE	REPLY (EN02)
LH	*ENERGY EFFICIENT – ENERGY STAR – OFFICE EQUIPMENT – PRINTERS, SCANNERS, AND ALL-IN-ONES*
HV	*ENERGY EFFICIENT – FEMP- LOW STANDBY POWER - OFFICE EQUIPMENT – FAX/PRINTER*
HU	*ENERGY EFFICIENT – FEMP- LOW STANDBY POWER - OFFICE EQUIPMENT - PRINTERS*
FY	*ENERGY EFFICIENT- FEMP - OFFICE EQUIPMENT - PRINTERS*
NR	*REVIEWED – DOES NOT MEET SOME ENAC CRITERIA*

SMPR *   B   SLEEP MODE POWER RATING IN WATTS

NOTE: If Reply Code HU was entered for MRC ENAC, reply to MRC SMPR.

Definition: THE RATED POWER THAT THE ITEM CONSUMES WHILE IN
SLEEP MODE, MEASURED IN WATTS..

MRC	Mode Code	Requirements

Reply Instructions: Enter the numeric value. (e.g., SMPRB60.0)

ELRN *   G   EXTRA LONG REFERENCE NUMBER

Definition: A REFERENCE NUMBER EXCEEDING 32 POSITIONS.

Reply Instructions: Enter the entire reference number. Do not include the 5-position Commercial and Government Entity (CAGE) Code unless there is more than one extra long reference number on the NSN, (e.g., ELRNGANN112036BIL060557LEN313605UZ62365*).

If there is more than one extra long reference number on the NSN, include the CAGE or NCAGE and separate each reference by using the "&" character, (e.g., 28480 ANN112036BIL060557LEN313605UZ62365 & S1234 NN112036BIL060557LEN313605UZ62365).

In determining quantity of characters in the reference number, count will be made after modification in accordance with Volume 2, Chapter 9, FLIS Procedures Manual, DoD 4100.39-M.

CLQL *   G   COLLOQUIAL NAME

Definition: A COMMON USAGE NAME BY WHICH AN ITEM IS KNOWN.

Reply Instructions: Enter the reply in clear text. (e.g., CLQLGWOVEN WIRE CLOTH*)

AGAV *   G   END ITEM IDENTIFICATION

Definition: THE NATIONAL STOCK NUMBER OR THE IDENTIFICATION INFORMATION OF THE END EQUIPMENT FOR WHICH THE ITEM IS A PART.

Reply Instructions: Enter the applicable reply in clear text.

(e.g., AGAVG3930-00-000-0000*;

AGAVGFORKLIFT TRUCK, SMITH CORPORATION, MODEL 12, TYPE A*)

CXCY *   G   PART NAME ASSIGNED BY CONTROLLING AGENCY

Definition: THE NAME ASSIGNED TO THE ITEM BY THE GOVERNMENT AGENCY OR COMMERCIAL ORGANIZATION CONTROLLING THE DESIGN OF THE ITEM.

MRC   Mode Code   Requirements

Reply Instructions: Enter the reply in clear text. (e.g., CXCYGLINE PROCESSOR
CONTROL BOARD*)

Reply Tables

Table 1 - NONDEFINITIVE SPEC/STD DATA

NONDEFINITIVE SPEC/STD DATA

REPLY CODE	REPLY (AD08)
AL	ALLOY
AN	ANNEX
AP	APPENDIX
AC	APPLICABILITY CLASS
AR	ARRANGEMENT
AS	ASSEMBLY
AB	ASSORTMENT
BX	BOX
CY	CAPACITY
CA	CASE
CT	CATEGORY
CL	CLASS
CE	CODE
CR	COLOR
CC	COMBINATION CODE
CN	COMPONENT
CP	COMPOSITION
CM	COMPOUND
CD	CONDITION
CS	CONSTRUCTION
DE	DESIGN
DG	DESIGNATOR
DW	DRAWING NUMBER
EG	EDGE
EN	END
FY	FAMILY
FG	FIGURE
FN	FINISH
FM	FORM
FA	FORMULA
GR	GRADE
GP	GROUP
BA	IMAGE COLOR
NS	INSERT
TM	ITEM
KD	KIND
KT	KIT
LG	LENGTH
LT	LIMIT
MK	MARK
AA	MARKER
ML	MATERIAL

REPLY CODE	REPLY (AD08)
BB	MAXIMUM DENSITY
MH	MESH
ME	METHOD
BC	MINIMUM DENSITY
MD	MODEL
MT	MOUNTING
NR	NUMBER
PT	PART
PN	PATTERN
PC	PHYSICAL CONDITION
PS	PIECE
PL	PLAN
PR	POINT
QA	QUALITY
RN	RANGE
RT	RATING
RF	REFERENCE NUMBER
SC	SCHEDULE
SB	SECTION
SL	SELECTION
SE	SERIES
SV	SERVICE
SX	SET
SA	SHADE
SH	SHAPE
SG	SHEET
SZ	SIZE
PZ	SPECIES
SQ	SPECIFICATION SHEET
SD	SPEED
ST	STYLE
SS	SUBCLASS
SF	SUBFORM
SP	SUBTYPE
SN	SURFACE CONDITION
SY	SYMBOL
SM	SYSTEM
TB	TABLE
TN	TANNAGE
TP	TEMPER
TX	TEXTURE
TK	THICKNESS
TT	TREATMENT
TR	TRIM
TY	TYPE
YN	UNIT

REPLY CODE	REPLY (AD08)
VA	VARIETY
WT	WEIGHT
WD	WIDTH

Reference Drawing Groups

No table of contents entries found.

OUNCE TO DECIMAL OF A POUND CONVERSION CHART

OUNCES	POUNDS
1	0.062
2	0.125
3	0.188
4	0.250
5	0.312
6	0.375
7	0.438
8	0.500
9	0.562
10	0.625
11	0.688
12	0.750
13	0.812
14	0.875
15	0.938
16	1.000

FIIG Change List

FIIG Change List, Effective September 4, 2009.

Revised Replies FY and HU for MRC ENAC.

Add Replies LH, HV, and NR for MRC ENAC.